

ZU725T

Ultra bright professional installation laser projector









- 7800 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorized lens shift Ideal for a simple set-up
- Large zoom range Motorized zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 7800 lumens with 4K and HDR compatibility, the ZU725T features a dust-resistant IP5X certified optical engine for 24/7 operation

capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.6x zoom make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

Specifications

UPC: 796435 44 656 7, EAN: 5055387666955, Colour: Black

Display/image Display technology

DLP

Resolution WUXGA (1920x1200) 7,800 lumens Brightness 3.000.000:1 Contrast ratio Contrast ratio - full on/off 1.100:1 Native aspect ratio 16:10 Aspect ratio - compatible 4:3,16:9,16:10

Keystone correction -30°

horizontal

Keystone correction - vertical 95% Uniformity

 $1.27m \sim 7.62m$ (50" ~ 300 ") diagonal Screen size

Lamp info

Light source type DuraCore Laser LASER life 30,000 hours

Optical Throw ratio

1.25:1 ~ 2:1 Projection distance (m) 1.33m - 13.06m 1.6 Zoom Zoom type Motorised 18.72~29.59 Focal length (mm)

Lens shift Vertical: +/-55%, Horizontal: +/-25%

Lens shift Yes - {{downloads_link}}

Connectivity Connections

Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D

support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm

 $\textbf{Outputs} \ 1 \ x \ \text{HDMI} \ 2.0, \ 1 \ x \ \text{3D sync}, \ 1 \ x \ \text{USB-A power} \ 1.5\text{A},$ 1 x Audio 3,5mm

Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x

No LAN - wireless networking

General

Noise level (typical) 34dB 36dB Noise level (max) Full 3D 3D

Security Security bar, Kensington Lock

OSD / display languages 9 languages: English, French, German, Italian, Portuguese,

Russian, Chinese (simplified), Spanish, Chinese (traditional)

24/7 operation Yes 360° operation Yes

Remote control Backlit ProAV remote

Speaker count Watts per speaker 10W

Networking

LAN - wireless networking No

LAN Yes

Power

Power supply AC 90 - 264V 50/60 Hz with PFC input

Power consumption (standby) 0.5W Power consumption (min) 260W 520W Power consumption (max)

Weight and dimensions

486 x 432.5 x 176 Dimensions (W x D x H) mm Gross weight 17.5 kg Net weight 14 kg





