

Sharp LD-E181-162
Indoor LED 1.8 mm 162" FullHD Bundle

Datasheet





High Impact. Streamlined Value

Bring the brilliance of fine-pitch LED to value-driven environments, without compromising on performance. Purpose-built for corporate meeting rooms and digital signage, the Sharp E Series delivers vivid content clarity and brightness for excellent visibility.

Available in standard-size bundles, it includes all the components needed for seamless integration of large format displays, free from distracting bezels. The slim, lightweight design supports easy installation, either wall-mounted or free-standing, while front access to all components simplifies maintenance. A durable metal chassis ensures long-term reliability, in line with Sharp's reputation for engineering quality.

An SoC-based controller enables wireless content sharing and seamless connectivity with external devices. Whether presenting or collaborating, the E Series supports intuitive operation and minimal setup.

Designed to meet the demands of modern visual communication, the E Series combines professionalgrade performance with streamlined deployment, bringing high-impact LED to a broader range of applications.

Benefits

Trouble-free installation – for wall mounted or freestanding deployments, the mechanical cabinet design makes installation quick and easy.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered viewing experience.

Front serviceable modules - with front access to the LED modules, maintenance is easy.

Low-profile integration – the super slim and light weight modules align with perfection to create a large digital canvas which integrates unobtrusively into any environment.

Product Information

Product Name	Sharp LD-E181-162
Product Group	Indoor LED 1.8 mm 162" FullHD Bundle
Order Code	81000832 (With Powerbar), 81000960 (No Powerbar)

Display

Pixel Configuration	3-in-1 SMD (Black)
LED type	SMD (1415)
Screen Size [inch/cm]	162 / 411.5
Aspect Ratio	16:9
Pixel Pitch [mm]	1.8
Brightness (max.) [cd/ m²]	800
Lifetime	100000 hrs (50% brightness)
Contrast Ratio (typ.)	5000:1
Viewing Angle [°]	140 horizontal / 140 vertical
Dimming Capability	256 levels
Colour Processing	16 bit
Colours [Trill.]	281
LED Driving Method	1/60 dynamic scan
Frame Rate [Hz]	50/60
Refresh Rate [Hz]	≤ 3840
Colour Temperature [K]	3000 - 9500

Screen Resolution

Resolution	1920 x 1080
Resolution per m ²	284444
Number of Pixel per module [dot]	320 x 180
Number of Pixel per card [dot]	80 x 180

Connectivity

Input Video Digital	1 x 3G SDI; 1 x DVI-D; 1 x HDMI
Input Control	1 x GenLock; 1 x LAN

Electrical

Total Power	1548 typ. / 4500 max.	
Consumption [W]		

Power Consumption typ. [W]	212 per m² (normal use)	
Power Consumption max. [W]	617 per m²	
Environmental Cond	litions	
Operating Temperature [°C]	-20 to 40	
Operating Humidity [%]	10 to 80	
Mechanical		
Dimensions (W x H x D) [mm] per module	600 x 337.5 x 29	
Dimensions (W x H x D) [mm]	3,612 x 2,037 x 50 without powerbar; 3,612 x 2,081 x 50 incl. powerbar	
Weight [kg]	215.8; 220.6 without powerbar	
Additional Features		
Shipping Content	1x LED Controller; LED Modules (36 Cabinets, 144 Pixel Cards); Overframe Kit (6x6); Pixel Card Removal Tool; Powerbar (depending on version); Spare Parts Kit; Wall mount (6x6)	
Special Characteristics	Flush Surface SMD Design; Single Data Receiving Cards; Single Power Supplies	
Manufacturer	SHARP	
Serviceability	Front Service	
IP Level	IP20	
Certifications	CE; ETL; FCC Class A; RoHS	
Warranty	2 years	

^{* 162} inch

Material





Aluminum Cabinet



FCC Class A

CE

RoHS

This document is $\ \odot$ 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered

trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are
excepted. 09.10.2025