

PRO MP275QPDG

BE YOUR WINDOW TO THE WORLD





SPECIFICATIONS

PANEL RESOLUTION REFRESH RATE 100Hz RESPONSE TIME 1ms (MPRT) / 4ms (GTG) PANEL TYPE BRIGHTNESS (NITS) 250 cd/m2 VIEWING ANGLE ASPECT RATIO CONTRAST RATIO ADOBE RGB / DCI-P3 / SRGB ACTIVE DISPLAY AREA (MM) PIXEL PITCH (H X V) SUFFACE TREATMENT DISPLAY COLORS COLOR BIT HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x DisplayPort 1.2a output 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports AUDIO PORTS 1x Headphone-out KENSINGTON LOCK SPEAKER 2x 2W VESA MOUNTING POWER TYPE POWER INPUT DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) CARTON DIMENSION (W X H X D)	PANEL SIZE	27"
RESPONSE TIME 1ms (MPRT) / 4ms (GTG) PANEL TYPE IPS BRIGHTNESS (NITS) 250 cd/m2 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1300:1 ADOBE RGB / DCI-P3 / SRGB 84% / 79% / 100% ACTIVE DISPLAY AREA (MM) 596.736(H) x 335.664(V) PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a output 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-B<	PANEL RESOLUTION	2560 x 1440 (WQHD)
PANEL TYPE IPS BRIGHTNESS (NITS) 250 cd/m2 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1300:1 ADDBE RGB / DCI-P3 / SRGB 84% / 79% / 100% ACTIVE DISPLAY AREA (MM) 596.736(H) x 335.664(V) PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) VIDEO PORTS 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER TYPE Internal Power Board POWER TYPE Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (FIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT)	REFRESH RATE	100Hz
BRIGHTNESS (NITS) 250 cd/m2 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1300:1 ADOBE RGB / DCI-P3 / SRGB 84% / 79% / 100% ACTIVE DISPLAY AREA (MM) 596.736(H) x 335.664(V) PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD 1x USB FGbps Type-B 4x USB FGbps Type-B 4x USB FGbps Type-A 4x USB FGbps Type-A 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100 ~ 240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (FIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~	RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1300:1 ADOBE RGB / DCI-P3 / SRGB 84% / 79% / 100% ACTIVE DISPLAY AREA (MM) 596.736(H) x 335.664(V) PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm </th <th>PANEL TYPE</th> <th>IPS</th>	PANEL TYPE	IPS
ASPECT RATIO CONTRAST RATIO ADOBE RGB / DCI-P3 / SRGB ACTIVE DISPLAY AREA (MM) PIXEL PITCH (H X V) SURFACE TREATMENT DISPLAY COLORS COLOR BIT HDR Ready VIDEO PORTS USB Ports 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports LX USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS XENSINGTON LOCK SPEAKER VESA MOUNTING POWER TYPE INTERIOR POWER INPUT DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (FIVOT) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) 831 x 468 x 133 mm POWER 133 3 mm 1.300:1 300	BRIGHTNESS (NITS)	250 cd/m2
CONTRAST RATIO 1300:1 ADOBE RGB / DCI-P3 / SRGB 84% / 79% / 100% ACTIVE DISPLAY AREA (MM) 596.736(H) x 335.664(V) PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (FIVOT) -90° ~ 90° ADJUSTMENT (PIVOT) -90° ~ 233.9 mm (24.2 x 22.8 x 9.2 inch) BASTA Y 468 x 133 mm	VIEWING ANGLE	178°(H) / 178°(V)
ADOBE RGB / DCI-P3 / SRGB ACTIVE DISPLAY AREA (MM) PIXEL PITCH (H X V) SURFACE TREATMENT DISPLAY COLORS COLOR BIT HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK YES SPEAKER 2x 2W VESA MOUNTING POWER INPUT DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) 831 x 468 x 133 mm 831 x 468 x 133 mm 831 x 468 x 133 mm	ASPECT RATIO	16:9
ACTIVE DISPLAY AREA (MM) PIXEL PITCH (H X V) SURFACE TREATMENT DISPLAY COLORS COLOR BIT HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD USB Ports AUDIO PORTS LX USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS ENSINGTON LOCK SPEAKER VESA MOUNTING POWER TYPE Internal Power Board POWER INPUT DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (PIVOT) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DYNAMIC REFRESH (MM) 596.736(H) x 335.664(V) 0.2331(H) x 0.2331(V) Anti-glare 1.07B 1	CONTRAST RATIO	1300:1
PIXEL PITCH (H X V) 0.2331(H) x 0.2331(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 831 x 468 x 133 mm	ADOBE RGB / DCI-P3 / SRGB	84% / 79% / 100%
SURFACE TREATMENT DISPLAY COLORS COLOR BIT 10 bits (8 bits + FRC) HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) 831 x 468 x 133 mm CARTON DIMENSION (W X H X D) 831 x 468 x 133 mm	ACTIVE DISPLAY AREA (MM)	596.736(H) x 335.664(V)
DISPLAY COLORS 1.07B COLOR BIT 10 bits (8 bits + FRC) HDR SUPPORT HDR Ready 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 831 x 468 x 133 mm	PIXEL PITCH (H X V)	0.2331(H) x 0.2331(V)
COLOR BIT 10 bits (8 bits + FRC) HDR SUPPORT HDR Ready VIDEO PORTS 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 831 x 468 x 133 mm	SURFACE TREATMENT	Anti-glare
HDR SUPPORT ADDITION CARTON DIMENSION (W X H X D)	DISPLAY COLORS	1.07B
VIDEO PORTS 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD 1x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) 2x HDMI™ 2.0b (WQHD@100Hz) 1x DisplayPort 1.2a input 1x DisplayPort 1.2a	COLOR BIT	10 bits (8 bits + FRC)
VIDEO PORTS 1x DisplayPort 1.2a input 1x DisplayPort 1.2a output 1x Type-C (DP alt.) w/ 98W PD USB Ports 1x USB 5Gbps Type-B 4x USB 5Gbps Type-A AUDIO PORTS 1x Headphone-out KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	HDR SUPPORT	HDR Ready
AUDIO PORTS AUDIO PORTS Ix Headphone-out XENSINGTON LOCK Yes SPEAKER VESA MOUNTING POWER TYPE Internal Power Board POWER INPUT DYNAMIC REFRESH RATE TECHNOLOGY ADJUSTMENT (TILT) ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) AUDIO TO THE AUDI	VIDEO PORTS	1x DisplayPort 1.2a input 1x DisplayPort 1.2a output
KENSINGTON LOCK Yes SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	USB Ports	
SPEAKER 2x 2W VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	AUDIO PORTS	1x Headphone-out
VESA MOUNTING 100 x 100 mm POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	KENSINGTON LOCK	Yes
POWER TYPE Internal Power Board POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	SPEAKER	2x 2W
POWER INPUT 100~240V, 50~60Hz DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	VESA MOUNTING	100 x 100 mm
DYNAMIC REFRESH RATE TECHNOLOGY Adaptive-Sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	POWER TYPE	Internal Power Board
TECHNOLOGY Adaptive-sync ADJUSTMENT (TILT) -5° ~ 20° ADJUSTMENT (SWIVEL) -45° ~ 45° ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	POWER INPUT	100~240V, 50~60Hz
ADJUSTMENT (SWIVEL) ADJUSTMENT (PIVOT) ADJUSTMENT (HEIGHT) O ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm		Adaptive-Sync
ADJUSTMENT (PIVOT) -90° ~ 90° ADJUSTMENT (HEIGHT) 0 ~ 130 mm DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) CARTON DIMENSION (W X H X D) 831 x 468 x 133 mm	ADJUSTMENT (TILT)	-5° ~ 20°
ADJUSTMENT (HEIGHT) DIMENSION (W X H X D) CARTON DIMENSION (W X H X D) 0 ~ 130 mm 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	ADJUSTMENT (SWIVEL)	-45° ~ 45°
DIMENSION (W X H X D) 614.0 x 578.9 x 233.9 mm (24.2 x 22.8 x 9.2 inch) 831 x 468 x 133 mm	ADJUSTMENT (PIVOT)	-90° ~ 90°
(24.2 x 22.8 x 9.2 inch) (ARTON DIMENSION (W X H X D) 831 x 468 x 133 mm	ADJUSTMENT (HEIGHT)	0 ~ 130 mm
CARTON DIMENSION (W X H X D)	DIMENSION (W X H X D)	
	CARTON DIMENSION (W X H X D)	

FEATURES



Docking Monitor

Enhance your workspace with a docking monitor. Simplify connectivity, switch between tasks seamlessly, and boost productivity—all with a single monitor.



Simplify setup and streamline connectivity with daisy-chaining. Connect multiple monitors effortlessly for a more organized and productive workspace.



IPS Grade Panel

Instantly optimize the screen colors and brightness to ensure that you enjoy every detail at its best while creating your own on-line video



Webcam Cover

Safely Connect to the world with a webcam cover.



EyesErgo

EyesErgo An eye care solution designed with ergonomics in mind.



Productivity Intelligence App (P.I.)

The Productivity Intelligence App (P.I.) provides the smartest tool, KVM function, color & display mode to you while working with it every day



Control multiple devices via one set of keyboard, mouse, and MSI gaming monitor.



Adjustable Stand

Adjust the stand to the angle that is most suitable for you to keep yourself work comfortably.



100Hz High Refresh Rate

100 Hz Experience smooth gaming with a blazing fast 100Hz refresh rate, that gives you the upperhand in fast moving games.



PRO MP275QPDG

BE YOUR WINDOW TO THE WORLD

WEIGHT (NW / GW)	7.05 kg (16.53 lbs) / 10.24 kg (22.58 lbs)
CERTIFICATES	CB/CE Energy Star
VIDEO INPUT COMPATIBILITY	PC, Mac, PS5 [™] , PS4 [™] , Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
ACCESSORIES	1x HDMI™ Cable (2.0), 1x USB Type-C Cable, 1x USB Type-B to A cable, 1x Power Cord, 1x Quick Guide, 4x Stand Screw, 1x VESA Plate, 4x VESA Plate Screws
Note	HDMI™: 2560 x 1440 (Up to 100Hz) DisplayPort: 2560 x 1440 (Up to 100Hz) Type-C (DP Alt.): 2560 x 1440 (Up to 100Hz) w/ 98W PD HDMI™ CEC Support *Adobe RGB, DCI-P3 and sRGB follow CIE1976 Standard

CONNECTIONS



- 1. DC-Jack
- 2. 2x HDMI[™] 2.0b (WQHD@100Hz)
- 3. 1x DisplayPort 1.2a Input
- 4. 1x Type-C (DP Alt.) w/ 98W
- 5. 1x DisplayPort 1.2a Output
- 6. 1x USB 5Gbps Type-B
- 7. 1x LAN Port
- 8. 4x USB 5Gbps Type-A
- 9. Headphone-out
- 10. 1x Kensington Lock
- 11. 5-Way Navigator