

ProArt Display PA147CDV

Your creative workflow, dialed up



Key Features



Ultra-wide

32:9 ultra-wide Full HD (1920 x 550) IPS anti-glare pane



International color standard 100% sRGB / 100% Rec. 709 color space for digital images and video production



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the ΔE color difference value is less than 2



With MPP 2.0 support, you're able to use whip out a pen or stylus to jot down or sketch ideas whenever inspiration strike*



10-point Touch

Capacitive 10-point multi-touch capability and Windows 10 compatible**



USB Type-C Monitor

Dual USB-C and HDMI ports provide rich connectivity



Control Panel

Virtual Control Panel Integrate Software provides shortcut and customized hotkey to enhance productivity***



ASUS Dial

Intuitive ASUS Dial control integrate software and support Microsoft Dial provides shortcut and customized hotkey to enhance productivity***



Ergo Kick Stand

Ergo Kick Stand design provides intuitive tilt angle adjustment with landscape and portrait view


*ASUS Pen or stylus not included.

**10-point touch function will depend on the operating system.

***ProArt Creator Hub (ASUS Dial and Control Panel function) support Microsoft Windows only.

ProArt Display PA147CDV

Spec Sheet

Display	<p>Panel Size : 14-inch (35.56cm) Wide Screen (32:9) Display Viewing Area(HxV) : 344.22 x 98.60 mm Display Surface : Non-Glare Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.179mm Resolution : 1920x550 Color Space (sRGB) : 100% Color Space (Rec.709) : 100% Brightness (Typ.) : 400cd/m² Contrast Ratio (Typ.) : 1200:1 ASUS Smart Contrast Ratio (ASCR) : 100000000:1 Display Colors : 16.7M Response Time : 5ms (GTG) Refresh Rate (Max) : 60Hz Flicker-free : Yes Touch Screen : Yes, Capacitive 10-point multi-touch</p>
Video Feature	<p>Trace Free Technology : Yes ProArt Preset : Standard / sRGB / DCI-P3 / Rec. 709 / Scenery / Reading / Darkroom / User mode1 / User mode2 Color Temp. Selection : Yes (5 modes) Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y) Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes QuickFit : Yes HDCP : Yes, 1.4 Low Blue Light : Yes</p>
Audio Feature	<p>Speaker : Yes (1Wx2)</p>
IO ports	<p>USB-C x 2 HDMI(v1.4) x 1</p>  <p>The diagram shows three ports in a row: an HDMI (v1.4) port on the left, and two USB-C ports on the right.</p>
Signal Frequency	<p>Digital Signal Frequency : 24 KHz~83 KHz (H) / 23 Hz~60 Hz (V)</p>
Power Consumption	<p>Power On (Typical): < 5.05W Power Saving Mode : < 0.5W 100-240V, 50/60Hz</p>
Mechanical Design	<p>Tilt : 25° ~ 70° Pivot : 90° (Clockwise)</p>
Dimensions (Est.)	<p>Phys. Dimension with Stand (W x H x D) : 357.23 x 127.66 x 20.71 mm Box Dimension (W x H x D) : 440 x 290 x 92 mm</p>
Weight (Est.)	<p>Net Weight with Stand : 0.95 Kg Gross Weight : 2.3 Kg</p>
Accessories	<p>Power Adaptor, USB-C cable (optional), HDMI cable (optional), USB-C to USB-A Cable (optional), USB-C to USB-A adaptor (optional), Calibration Report, Quick Start Guide, Warranty Card, ProArt Sleeve</p>
Compliance Standard	<p>Energy Star®, FCC, UL/cUL, CB, CE, ErP, WEEE, BSMI, RCM, VCCI, J-MOSS, KCC, BIS, RoHS, CEC, WHQL Windows 7/10/11, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified</p>

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice

