

MPN: POEINJ-60W-USBC

Gigabit PoE to USB-C Converter 60W

POEINJ-25W-USBC is an indoor PoE rated networking converter, special convert power&data from PoE to Type-C devices. It is with 1 PoE port for 802.3bt standard input and 1 Type-C port for power output and 1 RJ45 port for data output. The dataspeed is 10/100/1000Mbps (Gigabit).This converter ouput total 60W for Type-C PDs, and the voltage output from 5V-20V base on the required of your Type-C PDs. It is designed with OVP,OCP, SCP, then worked safty for the Type-C PDs, such as computers, Ipad, Macbook, Google Wifi etc.

- Designed with PVP, OCP, SCP
- Designed for Computers, iPads, MacBook, Google Wifi etc.
- Material : Black Metal



Specifications

| | | |
|----------------------------------|--|---|
| Features | Certification | CE, FCC, UL & RoHS |
| | Easy to install | Yes |
| | LED indicators | Yes |
| | Maximum operating distance | 100 m |
| | Plug and Play | Yes |
| | Power protection features | Over current, Under voltage, Short circuit, Under power |
| | Product colour | Black |
| | RoHS compliance | Yes |
| | Surge protection | Yes |
| | Wall mountable | Yes |
| | Network | Cable standard |
| Cable types supported | | Cat5e, Cat6, Cat6a, Cat7, Cat8.1 |
| Cabling technology | | 10/100/1000BaseT |
| Ethernet interface type | | Gigabit Ethernet |
| Ethernet LAN data rates | | 10, 100, 1000 Mbit/s |
| Networking standards | | IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3bt |
| Power over Ethernet (PoE) | | Yes |
| Operational conditions | Operating relative humidity (H-H) | 20 - 80 % |
| | Storage temperature (T-T) | -20 - 70 °C |
| Package dimensions | Depth (package,cm) | 5 cm |
| | Gross Weight (Package, kg) | 0.53 kg |
| | Height (package,cm) | 18 cm |
| | Width (package,cm) | 16 cm |
| Packaging content | Number of products included | 1 pc(s) |
| Ports & interfaces | DC-in jack | Yes |
| | Ethernet LAN (RJ-45) ports | 1 |
| | Other connection | USB Type C |

| | | |
|---------------------------|---|--------------|
| Power | AC adapter input voltage | 100 - 240 V |
| | Input current | 3 A |
| | Output current | 3 A |
| | Output power | 60 Watt |
| | Power over Ethernet (PoE) power per port | 60 Watt |
| | Power plug type | Type F |
| | Total Power over Ethernet (PoE) budget | 60 Watt |
| Product dimensions | Net Weight (Product, kg) | 0.38 kg |
| Vendor information | Brand Name | MicroConnect |
| | Warranty | 2 Year(s) |

Other images

