

MPN: POEINJ-60W-UK

## 60W 802.3af/at PoE Injector UK

The POEINJ-60W is a single-port Gigabit PoE (Power over Ethernet) device with two RJ45 ports, one port for the Ethernet data input, another port for the integrated data and power supply output. Since the power supply itself does not have the data switch function, it needs to work together with a Network switch. It mixes the data of the network switch with the power supply, and transmits the data and the power supply to the remote powered terminal through the network cable. This can solve the layout restrictions due to the engineering power line. The device can provide PoE power supply to those Ethernet devices conforming to the IEEE802.3af/atPoE++ international standard, such as routers, switches, wireless APs, VoIP phones, industrial network terminals, and network cameras etc. It provides efficient engineering solutions for locations where power is not available at the remote end or where the use of Ethernet cable power increase system reliability and simplify equipment installation.



- Power protection for input overvoltage/under voltage, output over voltage, and each output over current short circuit protection and other functions
- System reliability : MTBF > 100k hours
- Conducted interference (CE) radiated interference (RE), Accord with EN55032, EN55024 standard
- Active PoE Injector

## Specifications

Features	Certification	CE, FCC, UL
	LED indicators	Yes
	Plug and Play	Yes
	Power protection features	Over current, Over voltage, Short circuit, Under power
	Product colour	Black
	RoHS compliance	Yes
Network	Cable standard	Cat5
	Cable types supported	Cat5
	Ethernet interface type	Gigabit Ethernet
	Ethernet LAN data rates	1000 Mbit/s
	Networking standards	IEEE 802.3af, IEEE 802.3i, IEEE 802.3x
	Power over Ethernet (PoE)	Yes
Operational conditions	Operating relative humidity (H-H)	20 - 80 %
	Operating temperature (T-T)	0 - 40 °C
	Storage temperature (T-T)	-20 - 70 °C
Package dimensions (verified)	Depth Verified	14,3 cm
	Gross Weight Verified	0,558 kg
	Height Verified	7,5 cm
	Width Verified	17 cm
Packaging content	Number of products included	1 pc(s)

Ports & interfaces	DC-in jack	Yes
	Ethernet LAN (RJ-45) ports	2
Power	AC adapter input voltage	100 - 240 V
	Power over Ethernet (PoE) power per port	60 W
	Power over Ethernet (PoE) voltage	55 V
	Power plug type	Type G
	Suitable for use in country/location	United Kingdom
Product dimensions	Net Weight (Product, kg)	0,38 kg
	Product Depth	3,35 cm
	Product Height	14,55 cm
	Product Width	6,58 cm
Technical details	Sustainability certificates	RoHS
Vendor information	Brand Name	MicroConnect
	Warranty	2 Year(s)

## Other images

