



# 16/24-Port 10/100Mbps Switch

TL-SF1016DS / TL-SF1024D

## ■ Overview

The TL-SF1016DS/TL-SF1024D 10/100Mbps Switch is designed to meet the needs of the most demanding workgroup and departmental connectivity requirements. All 16/24 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the TL-SF1016DS/TL-SF1024D can save up to 60%/75%\* of the power consumption and 80% of the packaging material can be recycled, making it an eco-friendly solution for your business network.

**Green Technology**

- Saving power 75%/70%/60%
- Recyclable packaging material

**High Performance**

- IEEE 802.3x flow control
- Non-blocking switching architecture
- 3.2/4.8 Gbps Switching Capacity Store and forward
- Auto-MDI/MDIX
- Auto-negotiation
- MAC address auto-learning and auto-aging

**Easy to use**

- Plug and Play design
- Quiet/Fanless design



# 16/24-Port 10/100Mbps Switch

## TL-SF1016DS / TL-SF1024D

**TP-LINK Green Technology**

This new generation The TL-SF1016DS/TL-SF1024D 10/100Mbps Switch features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

**High Performance**

Featuring non-blocking switching architecture, TL-SF1016DS/TL-SF1024D forwards and filters packets at full wire-speed for maximum throughput. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make TL-SF1016DS/TL-SF1024D work reliably.



**Easy to Use**

The auto features of this switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10 or 100Mbps) and intelligently adjusts for compatibility and optimal performance.



- Details:<http://www.tp-link.com/support/Localesupport.asp>
- German/Austrian/Swiss users are not included

**Specifications:**

Product Picture		
Model	TL-SF1016DS	TL-SF1024D
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Network Ports	16*10/100Mbps RJ45 ports	24*10/100Mbps RJ45 ports
Auto Negotiation	YES	YES
Auto MDI/MDIX	YES	YES
Systems	Windows 2000/XP/Vista/7/Linux/MAC OS	Windows 2000/XP/Vista/7/Linux/MAC OS
Forwarding Mode	Store and Forward	Store and Forward
Switch Capacity	3.2 Gbps	4.8 Gbps
MAC Address Table	8 K	8 K
Flow Control	YES	YES
Fanless	YES	YES
Power Saving	Up to 65%	Up to 75%
LED	Power、100Mbps、Link/Act	Power、100Mbps、Link/Act
Dimensions	294*180*44 mm	294*180*44 mm
Operating Temperature	0°C~40°C (32°F~104°F)	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)	-40°C~70°C (-40°F~158°F)
Operating Humidity	10%~90% non-condensing	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing	5%~90% non-condensing
Ordering Information	16-port 10/100Mbps switch	24-port 10/100Mbps switch

\* Maximum power savings when compared to a TP-LINK conventional switch, the real saving rate may vary based on the usage condition.