


HD28i

Big screen sports entertainment









- Ideal for daytime sports viewing Powerful 4000 lumens
- Amazing colour Bring the match to life with bright vivid images
- Easy connectivity HDMI and USB power

reactions.

• All-in-one solution - Built-in audio for ultimate convenience

Immerse yourself in the game with the HD28i and experience every moment on the big screen. Convenient and easy to set up, this compact

high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting Amazing colour technology, it delivers accurate true-to-life colour reproduction for sports and movie lovers. It also has low input latency - perfect for games and fast-moving events that rely on rapid



Specifications

EAN: 5055387666481, Colour: White

Display/image
Display technology

DLP™

Resolution 1080p Full HD (1920x1080)

 Brightness
 4,000 lumens

 Contrast ratio
 50,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3

 Keystone correction - vertical
 +/-40°

 Horizontal scan rate
 15:3 ~ 91.1Khz

 Vertical scan rate
 24 ~ 85f120 for 3DIHz

Uniformity 75%

Screen size 0.85m ~ 7.77m (33.5" ~ 306") diagonal

Lamp info
Light source type Lamp
Lamp watts 220

Lamp life hours (up to) 5000 (Bright), 6500 (Dynamic), 6000 (Eco), 7000 (Eco+), 10000 (Education)

Lamp life (education) 10,000 hours

Optical

 Throw ratio
 1.47:1 ~ 1.63:1

 Projection distance (m)
 1.2m - 10m

 Zoom
 1.1

 Zoom type
 Manual

 Focal length (mm)
 21.86 ~ 24

 Native offset
 115%

Connectivity

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

x Composite video, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support + MHL

Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-

A power 1A

Control 1 x RS232

General

3D compatibility

Noise level (typical) 29dB Noise level (max) 31dB

PC compatibility
FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility
NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz

NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
Finnish, French, German, Greek, Hunggrian, Indonesian, Italian

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 2W

In the box

AC power cord

Remote control

Remote control Battery Basic user manual

HDCast Pro, QuickCast Bundle, QuickCast starter kit,

Power

Power supply $100 \sim 240 \text{V}, 50 \sim 60 \text{Hz}$ Power consumption (standby) 0.5 W

 Power consumption (min)
 204W

 Power consumption (max)
 266W

Weight and dimensions

Optional wireless models

 $\begin{array}{lll} \textbf{Dimensions (W x D x H) mm} & 298 \times 230 \times 96 \\ \textbf{Gross weight} & 3.31 \text{ kg} \\ \textbf{Net weight} & 2.82 \text{ kg} \end{array}$





